



### Scoring sawblades KON/FZ

**Application:**

For scoring with feed.

**Machine:**



Panel sizing saws with scoring unit and pressure beam.

**Workpiece material:**

Chipboard and fibre materials paper and plastic coated, veneered, laminated veneer lumber (e.g. plywood, multiplex plywood), alu composite panels (z.B. Alucobond®).

**Technical information:**

Scoring depth 1.50 - 2.00 mm. Scoring sawblade has to be selected according to the cutting width of the main sawblade.



**Scoring sawblades KON/FZ, HW design**

WK 804 2

Machine	D	SB	TDI	BO	NLA	Z	ZF	SW	$n_{max}$	WSS ID
	mm	mm	mm	mm	mm			Deg.	$min^{-1}$	
SCM	100	3.2	2.5	20		20	KON/FZ	5	22900	165625 ●
	100	3.2	2.5	22		20	KON/FZ	5	22900	165626 ●
	120	3.2	2.5	20		24	KON/FZ	5	19000	165627 ●
Panhans	125	4.4	3.5	20		24	KON/FZ	5	18300	165628 ●
Holz-Her	125	4.4	3.5	45		24	KON/FZ	5	18300	165629 ●
Anthon	180	4.4	3.5	20		28	KON/FZ	5	12700	165630 ●
Anthon	180	5.8	4.0	20		36	KON/FZ	5	12700	165631 ●
Holz-Her	180	4.4	3.5	30	2/10/60	30	KON/FZ	5	12700	165632 ●
Homag	180	4.4	3.5	45		36	KON/FZ	5	12700	165633 ●
Homag	180	4.8	3.5	45		36	KON/FZ	5	12700	165634 ●
Anthon	200	6.8	4.2	20		36	KON/FZ	5	11400	165635 ●
Homag	200	4.8	3.5	45		36	KON/FZ	5	11400	165636 ●
SCM	200	4.4	3.5	80	2/14/110	36	KON/FZ	5	11400	165637 ●
Homag	220	3.2	2.4	45		60	KON/FZ	5	10400	165638 ●
Panhans	250	4.4	3.5	30	2/10/60	42	KON/FZ	5	9100	165639 ●
Holz-Her	280	4.4	3.5	30	2/10/60	48	KON/FZ	5	9100	165640 ●